

JNS RNA 5916 needle roller bearings

How do you find the JNS RNA 5916 needle roller bearings specification? 53.975 mm da Manufacturers Online Free check

da	53.975 mm
Da	140 mm
Ca	57.785 mm
A1	88.9 mm
A2	134.938 mm
ba	32.544 mm
H	167.481 mm
H1	88.9 mm
H2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
L	330.2 mm
N1	22.225 mm
R1	53.181 mm
R2	21.431 mm
RG	3/8 NPT
PG	1/8 NPT
h	36.513 mm
Housing	SAF 613
Bearing	1313 EKTN9
Adapter sleeve assembly	SNW 113×2.1/8
Stabilizing ring	2 x SR-1613
Labyrinth ring	2 x LOR 31

PosiTrac Plus contact element	2 x B10724-32
End plug (suffix Y)	EPR 7
Max. speed for PosiTrac Plus seal	2600 r/min
P60°	83.2 kN
P90°	49.8 kN
P120°	30.2 kN
P150°	26.7 kN
P180°	31.6 kN
Pa	6.49 kN
Mass pillow block	17.1 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	175.77 g