

KBC 32307J tapered roller bearings

We Provide 35 mm D Extensive KBC 32307J tapered roller bearings Selection And Competitive Wholesale Pricing. 15 mm d

d	15 mm
D	35 mm
B	11 mm
rs min	0.6 mm
Radial clearance class	C3
Mass	0.04 kg
Dynamic load, C	7.75 kN
Static load, C0	3.6 kN
Fatigue limit load, Cu	0.16 kN
f0	12.7
Nlim (grease)	19,000 rpm
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.68 Hz
Characteristic outer ring frequency, BPF0	2.61 Hz
Characteristic inner ring frequency, BRFI	4.39 Hz
da min	19 mm
da max	20 mm
Da max	31 mm

ra max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.045
Product Group	B04270
Enclosure	2 Seals
Precision Class	ABEC 3 ISO P6
Material – Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	0 Degree
Preload	None
Raceway Style	Not Applicable
Cage Material	Steel
Rolling Element	Ball Bearing
Enclosure Type	Non Contact Seal
Flush Ground	No
Inch – Metric	Metric
Other Features	Single Row Deep Groove C3 Clearance Prelubricant
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Width; 2 Seals Enclosure; ABEC 3 ISO P6 Precision; Steel Ba
UNSPSC	31171502
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball Deep Groove
Width	0.433 Inch 11 Millimeter
Outside Diameter	1.378 Inch 35 Millimeter

Bore	0.591 Inch 15 Millimeter
------	----------------------------