

KBC 62/28DDF1 deep groove ball bearings

Request A Quote For SKF Manufacturer Name N/A Minimum Buy Quantity Your Special KBC 62/28DDF1 deep groove ball bearings Needs Today! Free 0.0 Inventory Quotes. ISO 9001 certified.

| | |
|-------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0.09 |
| EAN | 7316577068927 |
| Product Group | B04286 |
| Stud Profile | Male |
| Mounting Thread | M12 X 1.75 |
| Thread Direction | Right Hand |
| Rolling Element | Spherical Plain |
| Material – Outer Member | Steel |
| Material – Ball | Steel |
| Material – Liner | Bronze |
| Relubricatable | Yes |
| Enclosure | Open |
| Other Features | 3 Piece Zinc Plated Outer |
| Long Description | 12MM Bore; 12MM House Width; Male Stud Profile; M12 X 1.75; Right Hand Thread Direction; Spherical P |
| Inch – Metric | Metric |
| UNSPSC | 31171508 |
| Harmonized Tariff Code | 8483.30.80.55 |

| | |
|------------------------------|---------------------------------|
| Noun | Bearing |
| Keyword 3 | Rod End |
| Keyword String | Plain Spherical Rod End |
| Manufacturer Item Number | SAKAC 12 M |
| Weight / LBS | 0.187 |
| Housing Width | 0.472 Inch 12 Millimeter |
| d | 12 mm |
| Ball Width | 0.63 Inch 16 Millimeter |
| bore diameter: | 12 mm |
| ball material: | Steel |
| misalignment angle: | 13 ° |
| race material: | Bronze |
| shank thread length: | 32 mm |
| radial static load capacity: | 12.2 kN |
| rod end type: | Male Threaded |
| operating temperature range: | -30 to +180 °F |
| shank thread size: | M12x1.75 |
| head diameter: | 33 mm |
| thread direction: | Right Hand |
| head width: | 12 mm |
| grade: | Precision |
| ball width: | 16 mm |
| lubrication type: | With Lubrication Fitting |
| length to ball center: | 54 mm |
| housing material: | Zinc-Plated Steel |
| standards met: | ISO 12240-4:1998, DIN 3405:1986 |
| d2 max. | 33 mm |
| B | 16 mm |

| | |
|--------------------------------|----------------------|
| G | M 12 |
| C1 max. | 12.5 mm |
| h | 54 mm |
| α | 13 ° |
| dk | 22.2 mm |
| l1 min. | 32 mm |
| l2 max. | 72 mm |
| r1 min. | 0.3 mm |
| Basic dynamic load rating C | 12.2 kN |
| Basic static load rating C0 | 12.2 kN |
| Specific dynamic load factor K | 50 N/mm ² |
| Material constant KM | 330 |
| Mass rod end | 0.085 kg |