

KBC K203019PC needle roller bearings

KBC K203019PC needle roller bearings Deal is your source for 49,2 Width (mm) OEM 41,275 mm d and accessories. We sell Genuine at 41,275 Bore Diameter (mm) discount prices.

Bore Diameter (mm)	41,275
Width (mm)	49,2
d	41,275 mm
s1	30.2 mm
A1	14 mm
B	49,2 mm
G	14 mm
J	105 mm
L	137 mm
T	54,2 mm
A2	14 mm
Weight	2,2 Kg
Basic dynamic load rating (C)	33,2 kN
Basic static load rating (C0)	21,6 kN
Fatigue load limit (Pu)	0,915
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.152
EAN	7316577755001
Product Group	M06110
Number of Mounting Holes	4

Mounting Method	Set Screw
Housing Style	4 Bolt Square Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	9/16 Inch
Relubricatable	Yes
Insert Part Number	YAR 209-110-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Inch
Long Description	4 Bolt Square Flange Block; 1-5/8" Bore; 5.8" Bolt Circle; 4-1/8" Bolt Spacing; 1 Pie
Other Features	Single Row Standard Duty Wide Inner Race Open End Has Flinger Y Bearing
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	FY 1.5/8 TF
Weight / LBS	5
Nominal Bolt Circle Diameter Round	5.8 Inch 148 Millimeter
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter

Bolt Spacing	4.125 Inch 104.78 Millimeter
Bore	1.625 Inch 41.275 Millimeter
Length Thru Bore	1.938 Inch 49.225 Millimeter
Housing material	Cast iron
Da	119.1 mm
Db1	102 mm
Db2	112 mm
A	39 mm
A3	3.2 mm
A5	26.5 mm
N	16 mm
RG	1/4-28 UNF
R1	24.5 mm
DN	6.5 mm
SWN	7 mm
GN	1/4-28 SAE-LT
J6	123 mm
J7	33.5 mm
N4	4 mm
Basic dynamic load rating C	33.2 kN
Basic static load rating C0	21.6 kN
Fatigue load limit Pu	0.915 kN
Limiting speed	4300 r/min
Mass bearing unit	2.05 kg
Thread grub screw G2	5/16-24 UNF
Hexagonal key size for grub screw N	3.969 mm

Recommended tightening torque for grub screw	6.5 N·m
Recommended diameter for attachment bolts, mm G	14 mm
Recommended diameter for attachment bolts, inch G	0.5625 in
Housing	FY 509 M
Bearing	YAR 209-110-2F
End cover	ECY 209