

KOYO 2218-2RS self aligning ball bearings

LET OUR KOYO 2218-2RS self aligning ball bearings EXPERTS GET YOU THE 900x630x450 Size (mm) PARTS YOU NEED.

Size (mm)	900x630x450
Bore Diameter (mm)	900
Outer Diameter (mm)	630
Width (mm)	450
d	630 mm
D	900 mm
B	450 mm
C	425 mm
α	2 °
dk	813 mm
b	35 mm
b1	35 mm
M	13 mm
r1 – min.	3 mm
r2 – min.	6 mm
da – min.	661 mm
da – max.	677 mm
Da – min.	757 mm
Da – max.	850 mm
ra – max.	3 mm
rb – max.	6 mm
Basic dynamic load rating – C	24500 kN
Basic static load rating – C0	37500 kN

Specific factor dynamic load – K	80 N/mm ²
Specific factor static load – K ₀	120 N/mm ²
Constant – K _M	1055
Lubricant	Maintenance free – dry lubrication
Design (sliding contact surface combination)	Steel/PTFE FRP
Sealing solution	–
α	2 °
r ₁ min.	3 mm
r ₂ min.	6 mm
d _a min.	661 mm
d _a max.	677 mm
D _a min.	757 mm
D _a max.	850 mm
r _a max.	3 mm
r _b max.	6 mm
Basic dynamic load rating C	24500 kN
Basic static load rating C ₀	37500 kN
Specific dynamic load factor K	80 N/mm ²
Specific static load factor K ₀	120 N/mm ²
Material constant K _M	1055
Mass plain bearing	1015 kg