

KOYO 2307K self aligning ball bearings

Request A Quote For Your Special KOYO 2307K self aligning ball bearings Needs Today! Free Quotes. ISO 9001 220 mm da 242.887 mm db certified.

da	220 mm
db	242.887 mm
dc	211.137 mm
Da	399.999 mm
Ca	117.805 mm
A1	222.25 mm
A2	311.15 mm
S	4.763 mm
ba	90.487 mm
H	473.075 mm
H1	241.3 mm
H2	95.25 mm
L	831.85 mm
R1	130.175 mm
R2	46.831 mm
RG	1 NPT
PG	1/4 NPT
h	79.375 mm
Housing	SSAFS 244
Bearing	22244 CC/W33
Lock nut	N 44
Lock washer	W 44

Stabilizing ring	SR-44-38
Labyrinth ring (db shaft position)	LOR 179
Labyrinth ring (dc shaft position)	LOR 170
End plug (suffix Y)	EPR 24
Bearing limiting speed	2000 r/min
P60°	691 kN
P90°	414 kN
P120°	260 kN
P150°	236 kN
P180°	285 kN
Pa	185 kN
Mass pillow block	352 kg
Cap bolt	1 1/2-6 UNC
Cap bolt recommended tightening torque	4284.4 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	2749.95 g