

KOYO 24068RK30 spherical roller bearings

KOYO 24068RK30 spherical roller bearings Manufacturers , Online Wholesale 30 Bore Diameter (mm) 47 Outer Diameter (mm) Suppliers !

Bore Diameter (mm)	30
Outer Diameter (mm)	47
d	30 mm
Fw	30 mm
D	42 mm
D1	47 mm
C	30 mm
r min.	0,6 mm
C1	11 mm
da min.	40 mm
ra max.	0,6 mm
C2	9,5 mm
Weight	0,14 Kg
Dynamic load rating radial (C)	22,3 kN
Dynamic load rating axial (C)	20,4 kN
Static load rating radial (C0)	39,5 kN
Static load rating axial (C0)	42 kN
(Grease) Lubrication Speed	4300 r/min
dw	30 mm
rs min	0.6 mm
Dw	2.5 mm
Dw1	6.35 mm

Lw	15.8 mm
Lubrication hole on outer ring	Oui/Yes
Precision class	P0
Mass	0.14 kg
Cr	22.3 kN
Ca	20.4 kN
C0r	39.5 kN
C0a	42 kN
Nlim (grease)	4,300 rpm
Nlim (oil)	6,200 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
da min	40 mm
ras max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.144
Product Group	B04144