

KOYO 24072R spherical roller bearings

Welcome 44.45×101.6×34.925 Size (mm) to the KOYO 24072R spherical roller bearings online 101,6 Outer Diameter (mm) seller.

| | |
|-------------------------------|--------------------|
| Size (mm) | 44.45×101.6×34.925 |
| Bore Diameter (mm) | 44,45 |
| Outer Diameter (mm) | 101,6 |
| Width (mm) | 34,925 |
| d | 44,45 mm |
| D | 101,6 mm |
| T | 34,925 mm |
| B | 36,068 mm |
| C | 26,988 mm |
| a | 22,2 mm |
| r min. | 3,6 mm |
| r2 min. | 3,2 mm |
| da min. | 59 mm |
| Da | 89 mm |
| db min | 53 mm |
| ra max. | 3,6 mm |
| rb max. | 3,2 mm |
| Db | 95 mm |
| Weight | 1,35 Kg |
| Basic dynamic load rating (C) | 131 kN |
| Basic static load rating (C0) | 159 kN |
| (Grease) Lubrication Speed | 4000 r/min |

| | |
|-------------------------|---------------|
| (Oil) Lubrication Speed | 5300 r/min |
| Calculation factor (e) | 0,29 |
| Calculation factor (Y0) | 1,16 |
| Inventory | 0.0 |
| Manufacturer Name | KOYO |
| Minimum Buy Quantity | N/A |
| EAN | 0605790038198 |
| Weight / US pound | 7.49 |
| Product Group | B04334 |
| Bearing No. | 527/522 |
| r(min) | 3.6 |
| r1(min) | 3.2 |
| Cr | 164 |
| C0r | 159 |
| Cu | 24.8 |
| Grease lub. | 4000 |
| Oil lub. | 5300 |
| a(mm) | 22.2 |
| da | 59.0 |
| db | 53.0 |
| ra(max) | 3.6 |
| rb(max) | 3.2 |
| e | 0.29 |
| Y1 | 2.10 |
| Y0 | 1.16 |
| (Refer.) Mass (kg) | 1.35 |