

KOYO 2474/2420 tapered roller bearings

KOYO 2474/2420 tapered roller bearings, Units 0.0 Inventory N/A Minimum Buy Quantity and Housings CAD models , Manufacturing Service . Get SKF Manufacturer Name Your Free.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.573
EAN	7316572102602
Product Group	M06110
Number of Mounting Holes	4
Mounting Method	Set Screw
Housing Style	4 Bolt Square Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	YAR 207-106-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Inch
Long Description	4 Bolt Square Flange Block; 1-3/8" Bore; 5.1" Bolt Circle; 3-5/8" Bolt Spacing; 1 Pie

Other Features	Single Row Standard Duty Wide Inner Race Open End Has Flinger Y Bearing
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	FY 1.3/8 TF/W64
Weight / LBS	3.2
d	1.375 Inch 34.925 Millimeter
Bolt Spacing	3.625 Inch 92.08 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Nominal Bolt Circle Diameter Round	5.1 Inch 130 Millimeter
D	1.688 Inch 42.87 Millimeter
bore diameter:	1.3750 in
radial static load capacity:	3440 lbf
bolt center-to-center length:	3.6220 in
seal type:	M Seal & Flingers
overall length/diameter:	4.6460 in
length through bore:	1.6890 in
bore type:	Round
operating temperature range:	0 °F to 185 °F
duty type:	Standard Duty
finish/coating:	Uncoated
mounting type:	Four-Bolt Flange
series:	FY
housing material:	Cast Iron

application:	Metal manufacturing, Paper mills, Steel mills–plate, slab, strip, blast furnace, Overhead cran
locking device:	Set Screw
manufacturer upc number:	7316572102602
radial dynamic load capacity:	5733 lbf