

KOYO 32020JR tapered roller bearings

KOYO 32020JR tapered roller bearings Needs Analysis , Manufacturing Service . Get Your Free. 55 Bore Diameter (mm)

Bore Diameter (mm)	55
d	55 mm
Da	150.8 mm
s1	43.6 mm
A1	16 mm
B1	71.4 mm
G	16 mm
J	130 mm
L	162 mm
N	18 mm
T	74,6 mm
A2	16 mm
Weight	3,85 Kg
Basic dynamic load rating (C)	43,6 kN
Basic static load rating (C0)	29 kN
Fatigue load limit (Pu)	1,25
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	M06110
Housing material	Cast iron
Db1	122 mm

Db2	134 mm
A	47.5 mm
A3	3.2 mm
A5	34 mm
RG	1/4-28 UNF
R1	32 mm
DN	6.5 mm
SWN	7 mm
GN	1/4-28 SAE-LT
J6	148 mm
J7	45 mm
N4	4 mm
Basic dynamic load rating C	43.6 kN
Basic static load rating C0	29 kN
Fatigue load limit Pu	1.25 kN
Limiting speed	3600 r/min
Mass bearing unit	3.45 kg
Thread grub screw G2	M10x1
Hexagonal key size for grub screw N	5 mm
Recommended tightening torque for grub screw	16.5 N·m
Recommended diameter for attachment bolts, mm G	16 mm
Recommended diameter for attachment bolts, inch G	0.625 in
Housing	FY 511 M
Bearing	YEL 211-2F
End cover	ECY 211