

KOYO 322/32CR tapered roller bearings

Shop KOYO 322/32CR tapered roller bearings huge online discount inventory. 85 Bore Diameter (mm) and Import machinery parts your 85x180x77 Size (mm) car needs with Free Shipping and Free Extended Warranty.

| | |
|-------------------------------|-----------|
| Size (mm) | 85x180x77 |
| Bore Diameter (mm) | 85 |
| Outer Diameter (mm) | 180 |
| Width (mm) | 77 |
| d | 85 mm |
| D | 180 mm |
| T1 | 77 mm |
| T2 | 83 mm |
| d1 | 177 mm |
| r min. | 2,1 mm |
| A | 47 mm |
| C | 23 mm |
| D1 | 88 mm |
| D2 | 130 mm |
| D3 | 185 mm |
| R | 140 mm |
| da min. | 141 mm |
| Da max. | 124 mm |
| ra max. | 2 mm |
| Weight | 10,8 Kg |
| Basic dynamic load rating (C) | 307 kN |

| | |
|-------------------------------|-----------|
| Basic static load rating (C0) | 753 kN |
| (Grease) Lubrication Speed | 780 r/min |
| Bearing No. | 53417U |
| T | 83 |
| r(min) | 2.1 |
| Ca | 384 |
| Coa | 753 |
| Cu | 29.5 |
| Grease lub. | 780 |
| Oil lub. | 1200 |
| d1(max) | 177 |
| D1(min) | 88 |
| D2(min) | 130 |
| D3(min) | 185 |
| da(min) | 141 |
| Da(max) | 124 |
| ra(max) | 2 |
| (Refer.) Mass (kg) | 10.8 |