

KOYO 32219JR tapered roller bearings

What is KOYO 32219JR tapered roller bearings in mechanical engineering? Manufacturing Service . Upload 50 Bore Diameter (mm) your CAD 50x130x31 Size (mm) file for an instant.

Size (mm)	50x130x31
Bore Diameter (mm)	50
Outer Diameter (mm)	130
Width (mm)	31
d	50 mm
D	130 mm
B	31 mm
C	31 mm
r min.	2,1 mm
da min.	61 mm
Da max.	119 mm
ra max.	2 mm
Weight	1,88 Kg
Basic dynamic load rating (C)	83 kN
Basic static load rating (C0)	49,5 kN
(Grease) Lubrication Speed	5500 r/min
(Oil) Lubrication Speed	6600 r/min
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	2.035
EAN	0605790341977

Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	50MM Bore; 130MM Outside Diameter; 31MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6410
Weight / LBS	4.482
Bore	1.969 Inch 50 Millimeter
Outer Race Width	1.22 Inch 31 Millimeter
Outside Diameter	5.118 Inch 130 Millimeter
Bearing No.	6410
r(min)	2.1
Cr	104
C0r	49.5
Cu	4.10
f0	12.5
Grease lub.	5500

Oil lub.	6600
da(min)	61
Da(max)	119
ra(max)	2
(Refer.)Mass(kg)	1.88