KOYO 32932JR tapered roller bearings

offers a KOYO 32932JR tapered roller bearings Mounted Bearing Engineering Group selection of Genuine at Wholesale Prices. We are a KOYO 32932JR tapered roller bearings Certified Parts Retailer

| Engineering Group | Mounted Bearing |
|-------------------------|--------------------------|
| Shaft Size | 75 mm |
| Shaft Size Type | Metric |
| Full Timken Part Number | QMCW15J075SB |
| Locking Style | Eccentric |
| Weight | 22.00 lb |
| Housing Style | Piloted Flange Cartridge |
| UPC Code | 0883450062725 |
| Dimension BC | 7.50 in |
| Dimension C | 4.010 in |
| Dimension E | 5.30 in |
| Dimension B Fix | 1.81 in |
| Dimension B Exp | 1.89 in |
| Dimension F | 8.75 in |
| Dimension D | 6.38 in |
| Dimension H | 0.50 in |
| Dimension J (Bolt Size) | 0.625 in |
| Dimension M | 2.37 in |
| Dimension R | 0.06 in |
| Dimension S | 3.62 in |
| Dimension G | 6.375 in |

| Dimension K | 1.25 in |
|-------------------------------------|-----------|
| Dimension L Exp | 3.76 in |
| Dimension L Fix | 3.68 in |
| Dimension N | 1.88 in |
| CO — Static Load | 54100 lb |
| C — Dynamic Load (Basic) | 49900 lb |
| e — Geometry Factor | 0.22 |
| Y1 - Geometry Factor | 3.14 |
| Y2 - Geometry Factor | 4.67 |
| Oil Lubrication — M/N Seal | 1600 rpm |
| Oil Lubrication — T Seal | 2900 rpm |
| Oil Lubrication — B/C/O Seal | 1300 rpm |
| Grease Lubrication — M/N Seal | 1600 rpm |
| Grease Lubrication — T Seal | 2400 rpm |
| Grease Lubrication — B/C/O Seal | 1300 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0020 in |
| Eng Internal Radial Clearance — Min | 0.0020 |
| Eng Internal Radial Clearance — Max | 0.0031 |
| Pre Install Clearance Min | 0.0020 in |
| Pre Install Clearance Max | 0.0031 in |