

KOYO 332/32JR tapered roller bearings

KOYO 332/32JR tapered roller bearings 0.0 Inventory Manufacturers , Online Wholesale Suppliers !

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	4.22
EAN	7316577611666
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Stepped Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	22209
Seals	Trigard
Housing Configuration	1 Piece Solid
Inch – Metric	Inch
Other Features	Double Row Heavy Duty Locating Bearing Open End With Grub Screw

Long Description	2 Bolt Pillow Block; 1-3/4" Bore; 2-1/4" Base to Center Height; Stepped Sleeve Mount; Sphe
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SYE 1.3/4 NH
Weight / LBS	9.3
Bolt Spacing Minimum	6.75 Inch 171.45Millimeter
Bolt Spacing Maximum	7.25 Inch 184.15Millimeter
Nominal Bolt Center to Center	6.7 Inch 170 Millimeter
d	1.75 Inch 44.45 Millimeter
D	2.343 Inch 59.5 Millimeter
B	2.25 Inch 57.15 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
bore diameter:	1.7500 in
expansion type:	Non-Expansion Bearing (Fixed)
overall length:	8.8750 in
finish/coating:	Uncoated
overall height:	4.5000 in
overall width:	2-1/2 in
mounting:	Two-Bolt Base
seal type:	Triple Lip
bearing type:	Spherical Roller
radial dynamic load capacity:	23000 lbf
bore type:	Round
radial static load capacity:	24100 lbf
housing construction:	Solid Pillow Block

maximum rpm:	3700 RPM
base to bore centerline:	2.2500 in
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
end type:	Open
locking device:	Concentric Collar
series:	SYE
bolt center-to-center length:	6-3/4 to 7-1/4 in
replacement bearing:	22209
base width:	2-1/2 in