

# KOYO 3NC604YH4 deep groove ball bearings

Various types and 20x47x14 Size (mm) sizes to accommodate 47 Outer Diameter (mm) your KOYO 3NC604YH4 deep groove ball bearings requirements.

Size (mm)	20x47x14
Bore Diameter (mm)	20
Outer Diameter (mm)	47
Width (mm)	14
d	20 mm
D	47 mm
B	14 mm
C	14 mm
ra1 max.	0,6 mm
Angle ( $\alpha$ )	25 °
a	17 mm
r min.	1 mm
r1 min.	0,6 mm
2B	28 mm
da min.	25,5 mm
ra max.	1 mm
Db max	42,5 mm
Weight	0,2 Kg
Basic dynamic load rating (C)	23,6 kN
Basic static load rating (C0)	16,8 kN
(Grease) Lubrication Speed	14 000 r/min
Inventory	0.0

Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.206
EAN	4547359438154
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	30 Degree
Internal Clearance	C0-Medium
Number of Bearings	2 (1 Pair)
Mounting Arrangement	Duplex-Back to Back
Inch – Metric	Metric
Long Description	20MM Bore; 47MM Outside Diameter; 28MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Ba
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	7204DB
Weight / LBS	0.455
Outside Diameter	1.85 Inch   47 Millimeter
Width	1.102 Inch   28 Millimeter

Bore	0.787 Inch   20 Millimeter
bore diameter:	20 mm
precision rating:	ISO Class 0
outside diameter:	47 mm
cage material:	Steel
overall width:	28 mm
finish/coating:	Uncoated
contact angle:	30 °
inner ring width:	14 mm
duplex type:	Back to Back
maximum rpm (oil):	18000 rpm
internal clearance:	C0
maximum rpm (grease):	14000 rpm
closure type:	Open
outer ring width:	14 mm
operating temperature range:	-40 to 120 °C
fillet radius:	1 mm
radial dynamic load capacity:	23600 N
series:	72
radial static load capacity:	16800 N
manufacturer product page:	<a href="#">Click here</a>
bearing material:	High Carbon Chrome Steel