

KOYO 423X/414 tapered roller bearings

Browse KOYO 423X/414 tapered roller bearings Categories in the Manufacturers Online Free. including 65 mm d .

d	65 mm
D	140 mm
B	48 mm
E	124.5 mm
F	82.5 mm
rs min	2.1 mm
r1s min	2.1 mm
Radial clearance class	CN
Mass (without HJ ring)	3.46 kg
Dynamic load, C	248 kN
Static load, C0	287 kN
Fatigue limit load, Cu	34.7 kN
Nlim (oil)	4,800 rpm
Nlim (grease)	4,100 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.73 Hz
Characteristic outer ring frequency, BPF0	5.18 Hz
Characteristic inner ring frequency, BRFI	7.82 Hz

da min	76 mm
da max	81 mm
db min	85 mm
Da max	129 mm
ra max	2 mm
r1a max	2 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	3.48
EAN	4547359143829
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID

Long Description	65MM Bore; Straight Bore Profile; 140MM Outside Diameter; 48MM Width; Brass Cage Matetrial; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NU2313EG1
Weight / LBS	7.655
Outside Diameter	5.512 Inch 140 Millimeter
Width	1.89 Inch 48 Millimeter
Bore	2.559 Inch 65 Millimeter