

# KOYO 45256 tapered roller bearings

High Quality KOYO 45256 tapered roller bearings. Competitive Pricing. Accept Small 52 Outer Diameter (mm) Order. 20x52x15 Size (mm) Easy and Fast Shipping.

Size (mm)	20x52x15
Bore Diameter (mm)	20
Outer Diameter (mm)	52
Width (mm)	15
d	20 mm
D	52 mm
B	15 mm
C	15 mm
r min.	1,1 mm
da min.	26,5 mm
da max	28 mm
Da max.	45,5 mm
ra max.	1 mm
Weight	0,145 Kg
Basic dynamic load rating (C)	15,9 kN
Basic static load rating (C0)	7,9 kN
(Grease) Lubrication Speed	14 000 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.06
EAN	0029176016561

Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	20MM Bore; 52MM Outside Diameter; 15MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6304ZZ
Weight / LBS	0.142
Bore	0.787 Inch   20 Millimeter
Outer Race Width	0.591 Inch   15 Millimeter
Outside Diameter	2.047 Inch   52 Millimeter
bore diameter:	20 mm
snap ring included:	Without Snap Ring
outside diameter:	52 mm
internal clearance:	C0
overall width:	15 mm
dynamic load capacity:	15900 N
bore type:	Round

precision rating:	ABEC1, P0
closure type:	Double Shielded
finish/coating:	Uncoated
row type & fill slot:	Single Row Non-Fill Slot
cage material:	Steel Cage
SRI	4.81
hidYobi	6304ZZ
LangID	1
D_	52
SREX	0.04
B_	15
da min	26.5
hidTable	ecat_NSRDGB
SRE	5
mass	0.145
GRS rpm	14000
ra	1
SRIX	0.02
D_a	45.5
SRIN	0
C0	7.9
fo	12.4
SREN	0
DE_	45.525
Prod_Type3	DGBB_SR_ZZ
DA_	9.525
bomp	0
Z_	7
yobi	6304ZZ

C_conv	15900
ALPHA_	0
SDM_	36
r	1.1
KBRG	6141
SBRG	3
DI_	26.475