

KOYO 455/452 tapered roller bearings

KOYO 455/452 tapered roller bearings Manufacturers , Online Wholesale 49,2125 Bore Diameter (mm) Suppliers !

Bore Diameter (mm)	49,2125
Width (mm)	54
d	49,2125 mm
s1	37,3 mm
A	54 mm
B	54 mm
G	16 mm
H	114 mm
H1	57,2 mm
H2	22 mm
J	157 mm
L	203 mm
N	26 mm
N1	18 mm
Weight	2,85 Kg
Basic dynamic load rating (C)	35,1 kN
Basic static load rating (C0)	23,2 kN
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	3.103

EAN	7316571782638
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Stepped Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	YSP 210-115-2F/AH
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch – Metric	Inch
Other Features	Single Row Standard Duty Wide Inner Race Air Handling Anti Rotation Pin Has Flinger Y Be
Long Description	2 Bolt Pillow Block; 1-15/16" Bore; 2-1/4" Base to Center Height; Stepped Sleeve Mount; Ba
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SY 1.15/16 PF/AH
Weight / LBS	6.28
Bolt Spacing Maximum	6.5 Inch 165.1Millimeter
Base to Center Height	2.25 Inch 57.15 Millimeter

Nominal Bolt Center to Center	6.3 Inch 160 Millimeter
Bore	1.938 Inch 49.225 Millimeter
Length Thru Bore	2.125 Inch 53.975 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
Bolt Spacing Minimum	5.875 Inch 149.225Millimeter