

KOYO 46328A tapered roller bearings

170 Million used KOYO 46328A tapered roller bearings instantly searchable. Shop our large selection of parts based on brand, price, description, 25x62x17 Size (mm) and location. Order the with stock ... 62 Outer Diameter (mm)

| | |
|-------------------------------|-------------|
| Size (mm) | 25x62x17 |
| Bore Diameter (mm) | 25 |
| Outer Diameter (mm) | 62 |
| Width (mm) | 17 |
| d | 25 mm |
| D | 62 mm |
| B | 17 mm |
| C | 17 mm |
| Angle (α) | 30 ° |
| a | 4.1 mm |
| r min. | 1.1 mm |
| r1 min. | 0.6 mm |
| da min. | 32 mm |
| Da max. | 55 mm |
| ra max. | 1 mm |
| Weight | 0.245 Kg |
| Basic dynamic load rating (C) | 26,4 kN |
| Basic static load rating (C0) | 15,8 kN |
| (Grease) Lubrication Speed | 10000 r/min |
| Configuration | Single Row |
| Enclosure | Open |

| | |
|-------------------------|------------------|
| Bore Type | Cylindrical Bore |
| Bore Size | 25 mm |
| Outside Diameter | 62 mm |
| Width | 17 mm |
| Fillet Radius/Chamfer | 1.1 mm |
| r1 | 0.6 mm |
| Dynamic Load Rating | 26,400 N |
| Static Load Rating | 15,800 N |
| Limiting Speed – Grease | 10,000 rpm |
| Limiting Speed – Oil | 14,000 rpm |
| da1 (min) | 32 mm |
| da2 (min) | 30 mm |
| Da1 (max) | 55 mm |
| Da2 (max) | 57 mm |
| ra (max) | 1 mm |
| ra1 (max) | 0.6 mm |