

KOYO 47256 tapered roller bearings

KOYO 47256 tapered roller bearings 30 Bore Diameter (mm) with easy-to-use parts graphics, giving you the ability to check parts availability, 30x62x16 Size (mm) 62 Outer Diameter (mm) pricing, examine remanufactured options.

Size (mm)	30x62x16
Bore Diameter (mm)	30
Outer Diameter (mm)	62
Width (mm)	16
d	30 mm
D	62 mm
B	16 mm
C	16 mm
Angle (α)	30 °
a	5.3 mm
r min.	1 mm
r1 min.	0.6 mm
da min.	36 mm
Da max.	56 mm
ra max.	1 mm
Weight	0.210 Kg
Basic dynamic load rating (C)	22,5 kN
Basic static load rating (C0)	14,8 kN
(Grease) Lubrication Speed	10000 r/min
Configuration	Single Row
Enclosure	Open

Bore Type	Cylindrical Bore
Bore Size	30 mm
Outside Diameter	62 mm
Width	16 mm
Fillet Radius/Chamfer	1 mm
r1	0.6 mm
Dynamic Load Rating	22,500 N
Static Load Rating	14,800 N
Limiting Speed – Grease	10,000 rpm
Limiting Speed – Oil	13,000 rpm
da1 (min)	36 mm
da2 (min)	33 mm
Da1 (max)	56 mm
Da2 (max)	58.4 mm
ra (max)	1 mm
ra1 (max)	0.6 mm