

KOYO 5595R/5535 tapered roller bearings

Question KOYO 5595R/5535 tapered roller bearings ? Find what you need faster by entering 2.0 Inventory SKF Manufacturer Name N/A Minimum Buy Quantity your information .

| | |
|-------------------------|---|
| Inventory | 2.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 1.594 |
| EAN | 7316576624353 |
| Product Group | B00152 |
| Mounting Method | Shaft |
| Enclosure | Open |
| Rolling Element | Ball Bearing |
| Cage Material | Polyamide |
| Precision Class | ABEC 1 ISO P0 |
| Internal Clearance | C3-Loose |
| Number of Rows of Balls | Double Row |
| Other Features | Allowable Misalignment 3 Deg High Capacity Design |
| Long Description | 55MM Bore; Shaft Mount; 120MM Outside Diameter; 29MM Inner Race Width; 29MM Outer Race Width; Open; |
| Inch – Metric | Metric |
| UNSPSC | 31171532 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Self Aligning |

| | |
|--------------------------|-----------------------------|
| Manufacturer Item Number | 1311 ETN9/C3 |
| Weight / LBS | 3.51 |
| Inner Race Width | 1.142 Inch 29 Millimeter |
| Outer Race Width | 1.142 Inch 29 Millimeter |
| d | 2.165 Inch 55 Millimeter |
| D | 4.724 Inch 120 Millimeter |
| bore diameter: | 55 mm |
| precision rating: | Not Rated |
| outside diameter: | 120 mm |
| maximum rpm: | 7500 RPM |
| overall width: | 29 mm |
| cage material: | Fiberglass Reinforced Nylon |
| bore type: | Straight |
| finish/coating: | Uncoated |
| closure type: | Open |
| maximum misalignment: | 3 ° |
| internal clearance: | C3 |
| outer ring width: | 29 mm |
| dynamic load capacity: | 50.7 kN |
| fillet radius: | 2 mm |
| static load capacity: | 18 kN |
| series: | 1300 |