

KOYO 57180F4 tapered roller bearings

We work closely with 440x360x80 Size (mm) our KOYO 57180F4 tapered roller bearings manufacturing partners to bring the best value to customers.

| | |
|-------------------------------|------------|
| Size (mm) | 440x360x80 |
| Bore Diameter (mm) | 440 |
| Outer Diameter (mm) | 360 |
| Width (mm) | 80 |
| d | 360 mm |
| D | 440 mm |
| B | 80 mm |
| d1 | 391 mm |
| E | 419.8 mm |
| b1 | 9.4 mm |
| K | 5 mm |
| s | 6 mm |
| r1,2 – min. | 2.1 mm |
| da – min. | 371 mm |
| Da – max. | 429 mm |
| ra – max. | 2 mm |
| Basic dynamic load rating – C | 935 kN |
| Basic static load rating – C0 | 2550 kN |
| Fatigue load limit – Pu | 224 kN |
| Reference speed | 560 r/min |
| Limiting speed | 700 r/min |
| Calculation factor – kr | 0.2 |

| | |
|-----------------------------|---------|
| d1 ≈ | 391 mm |
| s max. | 6 mm |
| r1,2 min. | 2.1 mm |
| da min. | 371 mm |
| Da max. | 429 mm |
| ra max. | 2 mm |
| Basic dynamic load rating C | 935 kN |
| Basic static load rating C0 | 2550 kN |
| Fatigue load limit Pu | 224 kN |
| Calculation factor kr | 0.2 |
| Mass bearing | 26 kg |