

# KOYO 593S/592A tapered roller bearings

KOYO 593S/592A tapered roller bearings 65 Outer Diameter (mm) Manufacturers , Online 32x65x17 Size (mm) Wholesale Suppliers !

Size (mm)	32x65x17
Bore Diameter (mm)	32
Outer Diameter (mm)	65
Width (mm)	17
d	32 mm
D	65 mm
B	17 mm
C	17 mm
rn	0,5 mm
r min.	1 mm
da min.	37 mm
da max	40 mm
Da max.	60 mm
ra max.	1 mm
Weight	0,226 Kg
Basic dynamic load rating (C)	20,7 kN
Basic static load rating (C0)	11,6 kN
(Grease) Lubrication Speed	11 000 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.225

EAN	4547359553833
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	32MM Bore; 65MM Outside Diameter; 17MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	62/32ZZ/2A
Weight / LBS	0.498
Outer Race Width	0.669 Inch   17 Millimeter
Bore	1.26 Inch   32 Millimeter
Outside Diameter	2.559 Inch   65 Millimeter
bore diameter:	32 mm
precision rating:	ISO Class 0
outside diameter:	65 mm
finish/coating:	Uncoated
overall width:	17 mm
bearing material:	High Carbon Chrome Steel

bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	17 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	17 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	11000 rpm
internal clearance:	CN
fillet radius:	1 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	11000 RPM
dynamic load capacity:	20700 N
series:	62
static load capacity:	11600 N
manufacturer product page:	<a href="#">Click here</a>