

# KOYO 60/32N deep groove ball bearings

LET OUR KOYO 60/32N deep groove ball bearings 65 Bore Diameter (mm) EXPERTS 65x80x71 Size (mm) GET YOU THE PARTS YOU NEED.

Size (mm)	65x80x71
Bore Diameter (mm)	65
Outer Diameter (mm)	80
Width (mm)	71
da	65 mm
A	80 mm
B	71 mm
H	24 mm
H1	80 mm
H2	30 mm
J	230 mm
L	280 mm
N1	18 mm
S	2.5 mm
J6	254 mm
J7	29 mm
N4 – max.	8 mm
A3	73 mm
A5	35.5 mm
ba – min.	38 mm
ba – max.	65 mm
Basic dynamic load rating – C	193 kN
Basic static load rating – C0	216 kN

Fatigue load limit – Pu	24 kN
Limiting speed	3800 r/min
Calculation factor – e	0.24
Calculation factor – Y1	2.8
Calculation factor – Y2	4.2
Diameter – dm	92.5 mm
Basic Designation bearing	22213 E
Pa	20 kN
P0°	290 kN
P55°	380 kN
P90°	230 kN
P120°	155 kN
P150°	140 kN
P180°	210 kN
Mass bearing unit	8.7 kg
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	M06110
N	24 mm
ba min.	38 mm
ba max.	65 mm
N4 max.	8 mm
Basic dynamic load rating C	193 kN
Basic static load rating C0	216 kN
Fatigue load limit Pu	24 kN
Calculation factor e	0.24
Calculation factor Y1	2.8

Calculation factor Y2	4.2
Bearing mean diameter dm	92.5 mm
Basic bearing designation	22213 E
Attachment bolt diameter G	16 mm
Tightening torque for attachment bolts	200 N·m
Grub screws	4 x M 6
Tightening torque for grub screws	8 N·m
Grease quantity for relubrication	7 g
End cover	ECY 213