

KOYO 624-2RS deep groove ball bearings

With over 10170 full-service stores, our KOYO 624-2RS deep groove ball bearings inventory is extensive and our parts are priced 1219.2×879.475×933.45 Size (mm) right. within 24 hours. 1219,2 Bore Diameter (mm) This helps you maximize your productivity by saving time and your hard-earned dollars.

| | |
|-------------------------------------|-----------------------|
| Size (mm) | 1219.2×879.475×933.45 |
| Bore Diameter (mm) | 1219,2 |
| Outer Diameter (mm) | 879,475 |
| Width (mm) | 933,45 |
| d | 879.475 mm |
| D | 1219.2 mm |
| B | 933.45 mm |
| T | 838.2 mm |
| r3,4 – min. | 3.3 mm |
| Basic dynamic load rating – C | 28100 kN |
| Basic static load rating – C0 | 81500 kN |
| Fatigue load limit – Pu | 4750 kN |
| Comparative radial load rating – CF | 7500 kN |
| Comparative axial load rating – CFa | 1230 kN |
| Thrust factor – K | 1.76 |
| Calculation factor – e | 0.33 |
| Calculation factor – Y1 | 2 |
| Calculation factor – Y2 | 3 |
| Calculation factor – Y0 | 2 |
| Mass bearing | 3680 kg |

| | |
|-----------------------------------|----------|
| Design variant/feature | TQIT.1 |
| d1 ≈ | 1025 mm |
| D1 ≈ | 1162 mm |
| r1,2 min. | 4.8 mm |
| r3,4 min. | 3.3 mm |
| Basic dynamic load rating C | 28100 kN |
| Basic static load rating C0 | 81500 kN |
| Fatigue load limit Pu | 4750 kN |
| Comparative radial load rating CF | 7500 kN |
| Comparative axial load rating CFa | 1230 kN |
| Thrust factor K | 1.76 |
| Calculation factor e | 0.33 |
| Calculation factor Y1 | 2 |
| Calculation factor Y2 | 3 |
| Calculation factor Y0 | 2 |