

KOYO 6575R/6521 tapered roller bearings

KOYO 6575R/6521 tapered roller bearings, Units and Housings CAD 90 Outer Diameter (mm) models , 40x90x33 Size (mm) Manufacturing Service . Get Your Free.

Size (mm)	40x90x33
Bore Diameter (mm)	40
Outer Diameter (mm)	90
Width (mm)	33
d	40 mm
D	90 mm
B	33 mm
C	33 mm
r min.	1,5 mm
da min.	49 mm
da max	52 mm
Da min	77 mm
Da max.	81 mm
ra max.	1,5 mm
Weight	0,98 Kg
Basic dynamic load rating (C)	136 kN
Basic static load rating (C0)	153 kN
(Grease) Lubrication Speed	4500 r/min
(Oil) Lubrication Speed	6000 r/min
Calculation factor (e)	0,35
Calculation factor (Y0)	1,9
Calculation factor (Y2)	2,8

Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	1
EAN	0029176624353
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AH2308 (Specify bore)
Inch – Metric	Metric
Long Description	40MM Tapered Bore; 90MM Outside Diameter; 33MM Width; C0-Medium Clearance; Adapter Mount; Double Row
Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer Item Number	22308EAKE4
Weight / LBS	1
Width	1.299 Inch 33 Millimeter

Outside Diameter	3.543 Inch 90 Millimeter
Adapter Part Number	SNW108 H2308 HE2308 (Specify bore) Inch H2308 (Specify bore) Millimeter
Bore	1.575 Inch 40 Millimeter
Y3	1.9
hidYobi	22308EAKE4
LangID	1
Y1	1.9
D_	90
Y2	2.8
Macha rpm	9000
B_	33
da min	49
hidTable	ecat_NSSPHR
Oil rpm	6700
Y0	1.9
mass	0.98
GRS rpm	5300
ra	1.5
TSR rpm	5600
C0	153
DE_	80.585
X0	1
Prod_Type3	SRB_CTB_TB
X1	1
X2	0.67
SIR	12.7
e	0.35

DA_	13.2
bomp	22308EAKE4
Z_	14
ALP2	17
ALP1	13
ALP3	0
D_a max	81
D_a min	77
yobi	22308EAKE4
HPS	HPS
ALPHA_	0.232
SDM_	67.738
r	1.5
KBRG	2328
SBRG	23
DI_	54.891