

KOYO 7306B angular contact ball bearings

How do you find the KOYO 7306B angular contact ball bearings specification? Manufacturers Online 0.0 Inventory Free N/A Minimum Buy Quantity check

| | |
|---------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 60.835 |
| EAN | 7316576668494 |
| Product Group | M06288 |
| Number of Mounting Holes | 2 |
| Mounting Method | Tapered Adapter Sleeve |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Spherical Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Expansion |
| Mounting Bolts | 7/8 Inch |
| Relubricatable | Yes |
| Insert Part Number | 22226 E |
| Seals | Labyrinth |
| Housing Configuration | 2 Piece Split |
| Inch – Metric | Metric |
| Other Features | Double Row Heavy Duty |
| Long Description | 2 Bolt Pillow Block; 130MM Bore; 152.4MM Base to Center Height; Tapered Adapter Sleeve Mount; Spheri |

| | |
|-----------------------------------|------------------------------------|
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | SAF 22226 |
| Weight / LBS | 134 |
| Bolt Spacing Maximum | 16 Inch 406.4Millimeter |
| Bolt Spacing Minimum | 14.625 Inch 371.475Millimeter |
| Nominal Bolt Center to Center | 15.3 Inch 389 Millimeter |
| Actual Bolt Center to Center | 0 Inch 0Millimeter |
| D | 7.625 Inch 193.675 Millimeter |
| B | 6 Inch 152.4 Millimeter |
| d | 5.118 Inch 130 Millimeter |
| bore diameter: | 130 mm |
| seal type: | Labyrinth Seal |
| overall length: | 18.3750 in |
| base height: | 2.3750 in |
| overall height: | 11.6250 in |
| maximum operating temperature: | Max 210 °F |
| mounting: | Four-Bolt Base |
| maximum rpm: | 3600 rpm |
| bearing type: | Spherical Roller |
| lubrication type: | Lubrication Fitting |
| bore type: | Round |
| bolt size: | 1.0000 in |
| housing construction: | Split Pillow Block |
| series: | SAF222 |

| | |
|----------------------------|-----------------------------------|
| base to bore centerline: | 6.0000 in |
| replacement bearing: | 22226 E |
| housing material: | Cast Iron |
| weight: | 134 lbs |
| bearing material: | Cast Iron |
| manufacturer product page: | Click here |
| finish/coating: | Blue Alkyd/Acryl Paint (RAL 5001) |
| manufacturer upc number: | 7316576668494 |
| overall width: | 7.6250 in |
| da | 130 mm |
| db | 149.225 mm |
| dc | 125.412 mm |
| Da | 230 mm |
| Ca | 73.787 mm |
| A1 | 133.35 mm |
| A2 | 193.675 mm |
| S | 4.763 mm |
| ba | 57.944 mm |
| H | 295.275 mm |
| H1 | 152.4 mm |
| H2 | 60.325 mm |
| J min. | 371.475 mm |
| J max. | 406.4 mm |
| J1 | 82.55 mm |
| L | 466.725 mm |
| N1 | 25.4 mm |
| R1 | 79.375 mm |
| R2 | 36.513 mm |

| | |
|--|-------------|
| RG | 1/2 NPT |
| PG | 1/4 NPT |
| h | 59.531 mm |
| Housing | SAF 226 |
| Bearing | 22226 E |
| Lock nut | AN 26 |
| Lock washer | W 26 |
| Stabilizing ring | SR-26-0 |
| Labyrinth ring (db shaft position) | LOR 136 |
| Labyrinth ring (dc shaft position) | LOR 122 |
| End plug (suffix Y) | EPR 27 |
| Bearing limiting speed | 3600 r/min |
| P60° | 189 kN |
| P90° | 113 kN |
| P120° | 73.8 kN |
| P150° | 68.1 kN |
| P180° | 84.5 kN |
| Pa | 54.7 kN |
| Mass pillow block | 60.8 kg |
| Cap bolt | 2 x 1-8 UNC |
| Cap bolt recommended tightening torque | 400 N·m |
| Cap bolt, SAE grade | 5 |
| Eye bolt | 3/8-16 UNC |
| Appropriate attachment bolt size G | 0.875 in |
| Initial grease fill | 765.45 g |