

# KOYO 7306B angular contact ball bearings

How do you find the KOYO 7306B angular contact ball bearings specification? Manufacturers Online 0.0 Inventory Free N/A Minimum Buy Quantity check

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	60.835
EAN	7316576668494
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Tapered Adapter Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	7/8 Inch
Relubricatable	Yes
Insert Part Number	22226 E
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Metric
Other Features	Double Row   Heavy Duty
Long Description	2 Bolt Pillow Block; 130MM Bore; 152.4MM Base to Center Height; Tapered Adapter Sleeve Mount; Spheri

UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SAF 22226
Weight / LBS	134
Bolt Spacing Maximum	16 Inch   406.4Millimeter
Bolt Spacing Minimum	14.625 Inch   371.475Millimeter
Nominal Bolt Center to Center	15.3 Inch   389 Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter
D	7.625 Inch   193.675 Millimeter
B	6 Inch   152.4 Millimeter
d	5.118 Inch   130 Millimeter
bore diameter:	130 mm
seal type:	Labyrinth Seal
overall length:	18.3750 in
base height:	2.3750 in
overall height:	11.6250 in
maximum operating temperature:	Max 210 °F
mounting:	Four-Bolt Base
maximum rpm:	3600 rpm
bearing type:	Spherical Roller
lubrication type:	Lubrication Fitting
bore type:	Round
bolt size:	1.0000 in
housing construction:	Split Pillow Block
series:	SAF222

base to bore centerline:	6.0000 in
replacement bearing:	22226 E
housing material:	Cast Iron
weight:	134 lbs
bearing material:	Cast Iron
manufacturer product page:	<a href="#">Click here</a>
finish/coating:	Blue Alkyd/Acryl Paint (RAL 5001)
manufacturer upc number:	7316576668494
overall width:	7.6250 in
da	130 mm
db	149.225 mm
dc	125.412 mm
Da	230 mm
Ca	73.787 mm
A1	133.35 mm
A2	193.675 mm
S	4.763 mm
ba	57.944 mm
H	295.275 mm
H1	152.4 mm
H2	60.325 mm
J min.	371.475 mm
J max.	406.4 mm
J1	82.55 mm
L	466.725 mm
N1	25.4 mm
R1	79.375 mm
R2	36.513 mm

RG	1/2 NPT
PG	1/4 NPT
h	59.531 mm
Housing	SAF 226
Bearing	22226 E
Lock nut	AN 26
Lock washer	W 26
Stabilizing ring	SR-26-0
Labyrinth ring (db shaft position)	LOR 136
Labyrinth ring (dc shaft position)	LOR 122
End plug (suffix Y)	EPR 27
Bearing limiting speed	3600 r/min
P60°	189 kN
P90°	113 kN
P120°	73.8 kN
P150°	68.1 kN
P180°	84.5 kN
Pa	54.7 kN
Mass pillow block	60.8 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Eye bolt	3/8-16 UNC
Appropriate attachment bolt size G	0.875 in
Initial grease fill	765.45 g