

# KOYO 78225/78537 tapered roller bearings

We Provide Extensive KOYO 78225/78537 tapered roller bearings Selection And Competitive Wholesale 0.0 Inventory Pricing.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 9.879  |
| EAN                       | 0782475315369  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 4 Bolt Round Flange Cartridge  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | INS-S2-300L  |
| Seals                     | Metallic Labyrinth   |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | With Pilot   |
| Inch – Metric             | Inch   |
| Long Description          | 4 Bolt Round Flange Cartridge;<br>3" Bore; 7-1/2" Bolt Circle;<br>5-19/64" Bolt Spacing; 1 |

|                                    |   |
|------------------------------------|---|
| Other Features                     | Double Row   Has Flinger   With Set Screw |
| UNSPSC                             | 31171501                                  |
| Harmonized Tariff Code             | 8483.20.40.80                             |
| Noun                               | Bearing                                   |
| Keyword String                     | Flanged                                   |
| Manufacturer Item Number           | FC-S2-300LE                               |
| Manufacturer Internal Number       | 070739                                    |
| Weight / LBS                       | 21.76                                     |
| Cartridge Pilot Depth              | 1.25 Inch   31.75 Millimeter              |
| Nominal Bolt Circle Diameter Round | 7.5 Inch   190 Millimeter                 |
| Bolt Spacing                       | 5.297 Inch   134.544 Millimeter           |
| Cartridge Pilot Diameter           | 6.375 Inch   161.92 Millimeter            |
| d                                  | 3 Inch   76.2 Millimeter                  |
| D                                  | 3.594 Inch   91.288 Millimeter            |