## KOYO DC5052NR cylindrical roller bearings

What are the dimensions of a KOYO DC5052NR cylindrical roller bearings? 0.0 Inventory Manufacturing N/A Minimum Buy Quantity Service . Get Your Free, Instant Quote□□

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | SKF  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 3.68   |
| EAN                       | 7316576674587  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar                                      |
| Housing Style             | 2 Bolt Pillow Block                                    |
| Rolling Element           | Spherical Roller Bearing                               |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 1/2 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22209  |
| Seals                     | Garter Spring  |
| Housing Configuration     | 1 Piece Solid  |
| Inch — Metric             | Inch   |
| Other Features            | Double Row   Heavy Duty   Open<br>End   With Set Screw |

| Long Description              | 2 Bolt Pillow Block; 1-3/4"<br>Bore; 2-1/8" Base to Center<br>Height; Concentric Collar<br>Mount; S |
|-------------------------------|---|
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | SYR 1.3/4-3   |
| Weight / LBS                  | 8.1   |
| Bolt Spacing Minimum          | 5.188 Inch   131.775Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   OMillimeter  |
| В                             | 2.125 Inch   53.98 Millimeter   |
| Nominal Bolt Center to Center | 5.5 Inch   140 Millimeter   |
| D                             | 2.875 Inch   73.02 Millimeter   |
| d                             | 1.75 Inch   44.45 Millimeter  |
| Bolt Spacing Maximum          | 5.813 Inch   147.65Millimeter   |
| bore diameter:                | 1.7500 in   |
| bolt center-to-center length: | 5-1/2 in  |
| overall length:               | 7.3750 in   |
| base width:                   | 2-1/16 in   |
| overall height:               | 4.2500 in   |
| expansion type:               | Expansion Bearing (Floating)  |
| mounting:                     | Two-Bolt Base   |
| finish/coating:               | Uncoated  |
| bearing type:                 | Spherical Roller  |
| seal type:                    | Tri-Guard   |
| bore type:                    | Round   |
| radial dynamic load capacity: | 20000 lbf   |
| housing construction:         | Solid Pillow Block  |

| radial static load capacity: | 19600 lbf           |
|------------------------------|---------------------|
| base to bore centerline:     | 2.1250 in           |
| maximum rpm:                 | 2300 RPM            |
| duty type:                   | Standard Duty       |
| lubrication type:            | Lubrication Fitting |
| housing material:            | Cast Iron           |
| series:                      | SYR                 |
| locking device:              | Concentric Collar   |
| replacement bearing:         | 22209               |