

KOYO DLF 30 16 needle roller bearings

KOYO DLF 30 16 needle roller bearings, Units and Housings CAD models 110x200x38 Size (mm) , 200 Outer Diameter (mm) Manufacturing Service . Get Your Free.

| | |
|-------------------------------|------------------|
| Size (mm) | 110x200x38 |
| Bore Diameter (mm) | 110 |
| Outer Diameter (mm) | 200 |
| Width (mm) | 38 |
| d | 110 mm |
| D | 200 mm |
| B | 38 mm |
| C | 38 mm |
| Angle (α) | 15 ° |
| a – | 1.0 mm |
| r min. | 2.1 mm |
| r1 min. | 1.1 mm |
| 2B | 76 mm |
| da min. | 122 mm |
| Da max. | 193 mm |
| ra max. | 1 mm |
| Weight | 4.62 Kg |
| Basic dynamic load rating (C) | 277 kN |
| Basic static load rating (C0) | 315 kN |
| (Grease) Lubrication Speed | 4200 r/min |
| Bore Type | Cylindrical Bore |
| Enclosure | Open |

| | |
|-------------------------|-----------|
| Configuration | Duplex |
| Bore Size | 110 mm |
| Outside Diameter | 200 mm |
| Width | 38 mm |
| Fillet Radius/Chamfer | 2.1 mm |
| r1 | 1.1 mm |
| Dynamic Load Rating | 277,000 N |
| Static Load Rating | 315,000 N |
| Limiting Speed – Grease | 4,200 rpm |
| Limiting Speed – Oil | 5,700 rpm |
| da1 (min) | 122 mm |
| da2 (min) | 122 mm |
| Da1 (max) | 188 mm |
| Da2 (max) | 193 mm |
| ra (max) | 2 mm |
| ra1 (max) | 1 mm |