

KOYO EE222070/222126 tapered roller bearings

We work closely with our 0.0 Inventory KOYO EE222070/222126 tapered roller bearings manufacturing partners N/A Minimum Buy Quantity to bring the best value to customers.

| | |
|---------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| EAN | 0013992062482 |
| Weight / US pound | 0.01 |
| Product Group | B04144 |
| Number of Mounting Holes | 2 |
| Mounting Method | Clamp Collar |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Cylindrical Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Expansion |
| Mounting Bolts | 16 Millimeter |
| Relubricatable | Yes |
| Insert Part Number | LSE207BX |
| Seals | High Temperature Packing |
| Housing Configuration | 2 Piece Split |
| Inch – Metric | Inch |
| Other Features | Single Row Light Duty With Support Wide Inner Ring |
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.80 |

| | |
|-------------------------------|--|
| Noun | Bearing |
| Keyword String | Pillow Block |
| Weight / LBS | 28.28 |
| B | 3.15 Inch 80 Millimeter |
| Actual Bolt Center to Center | 9.2 Inch 234Millimeter |
| Bolt Spacing Minimum | 0 Inch 0Millimeter |
| d | 2.438 Inch 61.925 Millimeter |
| Nominal Bolt Center to Center | 9.2 Inch 234 Millimeter |
| D | 2.362 Inch 60 Millimeter |
| Bolt Spacing Maximum | 0 Inch 0Millimeter |
| Shaft Size | 2-7/16 in |
| Seal Type | High Temperature Packing |
| Bearing Type | Split Cylindrical Expansion Type |
| Support Type | Two-Bolt Plummer Block |
| Series Type | Light Series |
| Pillow/Plummer Block Style | Split Cylindrical Housed Unit – Standard |
| Bolt Size | 2 x M16 |
| Weight | 28 lb |
| Bearing – Housing – Seal | LSE207BXHHTPS |
| Bearing – Housing – Seal UPC | 013992062031 |
| Bearing UPC | 013992025890 |
| Dimension H | 3.150 in |
| Dimension H1 | 1.3 in |
| Dimension H2 | 7.1 in |
| Dimension J | 9.2 in |
| Dimension L | 11.0 in |
| Dimension M | 2.8 in |

| | |
|--------------------------|---|
| Housing Width | 4.0 in |
| Cr – Dynamic Load Rating | 23155 lbf |
| Cor – Static Load Rating | 25853 lbf |
| Maximum Speed | 3940 rpm |
| Note | This product line was formerly known as “Revolvo” |