

KOYO EE971354/972100 tapered roller bearings

How do I place an EMERGENCY order for a KOYO EE971354/972100 tapered roller bearings that 80 Bore Diameter (mm) I want to pick 80x35x21 Size (mm) up at a our store?

Size (mm)	80x35x21
Bore Diameter (mm)	80
Outer Diameter (mm)	35
Width (mm)	21
d	35 mm
D	80 mm
B	21 mm
D1	65.8 mm
F	46.2 mm
r1,2 – min.	1.5 mm
r3,4 – min.	1.1 mm
s	1.2 mm
da – min.	42 mm
da – max.	44 mm
db – min.	48 mm
Da – max.	72.2 mm
ra – max.	1.5 mm
rb – max.	1 mm
Basic dynamic load rating – C	75 kN
Basic static load rating – C0	63 kN
Fatigue load limit – Pu	8.2 kN
Reference speed	9500 r/min

Limiting speed	11000 r/min
Calculation factor – kr	0.15
D1 ≈	65.8 mm
r1,2 min.	1.5 mm
r3,4 min.	1.1 mm
s max.	1.2 mm
da min.	42 mm
da max.	44 mm
db min.	48 mm
Da max.	72.2 mm
ra max.	1.5 mm
rb max.	1 mm
Basic dynamic load rating C	75 kN
Basic static load rating C0	63 kN
Fatigue load limit Pu	8.15 kN
Calculation factor kr	0.15
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	0.47 kg
Angle ring	HJ 307 EC