

# KOYO HI-CAP ST4078-3LFT tapered roller bearings

Can't find what you're looking for KOYO HI-CAP ST4078-3LFT tapered roller bearings ? Our expert Representatives be in contact with you N/A Minimum Buy Quantity shortly! 0.0 Inventory

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REGAL BELOIT   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 12.621   |
| EAN                       | 0662288490128  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Tapered Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Seals                     | Felt Labyrinth   |
| Housing Configuration     | 2 Piece Split  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Heavy Duty   Single Collar   Has Flinger   With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 2-1/2" Bore; 3-1/4" Base to Center Height; Concentric Collar Mount; T |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | EDPBA 208-2  |
| Manufacturer Internal Number  | 552951   |
| Weight / LBS                  | 27.8   |
| d                             | 2.5 Inch   63.5 Millimeter   |
| Nominal Bolt Center to Center | 9.7 Inch   246.4 Millimeter  |
| Bolt Spacing Maximum          | 10.375 Inch   263.525Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| B                             | 3.25 Inch   82.55 Millimeter   |
| D                             | 3.31 Inch   84.074 Millimeter  |
| Bolt Spacing Minimum          | 8.5 Inch   215.9Millimeter   |