

KOYO K25X30X26ZW needle roller bearings

KOYO K25X30X26ZW needle roller bearings Product 50 mm d 16 mm B Brochures , Manufacturing Service . Get Your Free.

d	50 mm
D	80 mm
B	16 mm
rs min	1 mm
Radial clearance class	C4
Mass	0.26 kg
Dynamic load, C	21.8 kN
Static load, C0	16.6 kN
Fatigue limit load, Cu	0.75 kN
f0	15.5
Nlim (oil)	9,800 rpm
Nlim (grease)	8,400 rpm
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	7.31 Hz
Characteristic outer ring frequency, BPF0	6.06 Hz
Characteristic inner ring frequency, BRFI	7.94 Hz
da min	55 mm
Da max	75 mm
ra max	1 mm

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.268
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C4-Extra Loose
Inch – Metric	Metric
Long Description	50MM Bore; 80MM Outside Diameter; 16MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fil
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.55115
Inner Race Width	0 Inch 0 Millimeter
Bore	1.969 Inch 50 Millimeter
Outside Diameter	3.15 Inch 80 Millimeter
Outer Race Width	0.63 Inch 16 Millimeter