

# KOYO KCA160 angular contact ball bearings

KOYO KCA160 angular contact ball bearings with easy-to-use parts 0.0 Inventory graphics, giving you ASAHI BEARINGS Manufacturer Name the ability to check parts availability, pricing, examine remanufactured options.

|                           |                               |
|---------------------------|-------------------------------|
| Inventory                 | 0.0                           |
| Manufacturer Name         | ASAHI BEARINGS                |
| Minimum Buy Quantity      | N/A                           |
| Weight                    | 0.91                          |
| EAN                       | 0808250316632                 |
| Product Group             | M06110                        |
| Number of Mounting Holes  | 4                             |
| Mounting Method           | Set Screw                     |
| Housing Style             | 4 Bolt Round Flange Cartridge |
| Rolling Element           | Ball Bearing                  |
| Housing Material          | Nickel Coated Cast Iron       |
| Expansion / Non-expansion | Non-expansion                 |
| Mounting Bolts            | 10 Millimeter                 |
| Relubricatable            | Yes                           |
| Insert Part Number        | MUC205                        |
| Seals                     | Contact Seal                  |
| Housing Configuration     | 1 Piece Solid                 |
| Pilot Configuration       | With Pilot                    |
| Inch – Metric             | Metric                        |

|                                       |  |
|---------------------------------------|--|
| Long Description                      | 4 Bolt Round Flange Cartridge;<br>25MM Bore; 90MM Bolt Circle;<br>63.5MM Bolt Spacing; 1 Piece<br>Solid; Set |
| Other Features                        | Single Row   Spherical  <br>Normal Duty  |
| UNSPSC                                | 31171501   |
| Harmonized Tariff Code                | 8483.20.40.40  |
| Noun                                  | Bearing  |
| Keyword String                        | Flanged  |
| Weight / LBS                          | 2  |
| Bolt Spacing                          | 2.5 Inch   63.5 Millimeter   |
| Cartridge Pilot Depth                 | 0.236 Inch   6 Millimeter  |
| Nominal Bolt Circle Diameter<br>Round | 3.5 Inch   90 Millimeter   |
| D                                     | 1.339 Inch   34 Millimeter   |
| d                                     | 0.984 Inch   25 Millimeter   |
| Cartridge Pilot Diameter              | 2.756 Inch   70 Millimeter   |