

KOYO KUX090 2RD angular contact ball bearings

KOYO KUX090 2RD angular contact ball bearings Engineering Calculator , Manufacturing Service 20x47x20.600 Size (mm) . Get Your Free.

Size (mm)	20x47x20.600
Bore Diameter (mm)	20,000
Outer Diameter (mm)	47,000
Width (mm)	20,600
d	20,000 mm
D	47,000 mm
B	20,600 mm
C	20,600 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359580822
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal

Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	20MM Bore; 47MM Outside Diameter; 20.62MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0;
Other Features	Deep Groove Cartridge Type Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Al
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.34
Bore	0.787 Inch 20 Millimeter
Outside Diameter	1.85 Inch 47 Millimeter
Outer Race Width	0.812 Inch 20.62 Millimeter
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	20 mm
precision rating:	ISO Class 0
outside diameter:	47 mm
finish/coating:	Uncoated
overall width:	20.6 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	20.60 mm
row type & fill slot:	Single Row Non-Fill Slot

outer ring width:	20.60 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	10000 rpm
internal clearance:	CN
fillet radius:	1 mm
operating temperature range:	-40 to 120 °C
series:	632
dynamic load capacity:	5100 N
manufacturer product page:	Click here
static load capacity:	2390 N