

# KOYO L225849/L225810 tapered roller bearings

100% Authentic. KOYO L225849/L225810 tapered roller bearings  
0.0 Inventory Highest Quality. Certified Supplier.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | ASAHI BEARINGS  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 0.772   |
| EAN                       | 0808250195435   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Set Screw   |
| Housing Style             | 4 Bolt Square Flange Block  |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Nickel Coated Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 10 Millimeter   |
| Relubricatable            | Yes   |
| Insert Part Number        | MUC205  |
| Seals                     | Contact Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Metric  |
| Long Description          | 4 Bolt Square Flange Block;<br>25MM Bore; 99MM Bolt Circle;<br>70MM Bolt Spacing; 1 Piece<br>Solid; Set Screw |

|                                    |  |
|------------------------------------|--|
| Other Features                     | Single Row   Spherical   Normal Duty   Has Slinger |
| UNSPSC                             | 31171501   |
| Harmonized Tariff Code             | 8483.20.40.40                                      |
| Noun                               | Bearing  |
| Keyword String                     | Flanged  |
| Manufacturer Item Number           | MUCF205NP  |
| Weight / LBS                       | 2.01   |
| Nominal Bolt Circle Diameter Round | 3.9 Inch   99 Millimeter                           |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter                              |
| Bolt Spacing                       | 2.756 Inch   70 Millimeter                         |
| d                                  | 0.984 Inch   25 Millimeter                         |
| D                                  | 1.339 Inch   34 Millimeter                         |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter                              |