

KOYO M6317 deep groove ball bearings

How do I place an EMERGENCY order for a KOYO M6317 deep groove ball bearings that I want to pick up at 71.438 mm da a our store?

da	71.438 mm
Da	180 mm
Ca	69.799 mm
A1	111.125 mm
A2	173.037 mm
S	4.763 mm
ba	48.419 mm
H	222.25 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
J1	60.325 mm
L	387.35 mm
N1	22.225 mm
R1	65.088 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/8 NPT
h	44.45 mm
Housing	FSAF 617
Bearing	22317 EK

Adapter sleeve assembly	SNW 117×2.13/16
Stabilizing ring	SR-20-17
Labyrinth ring	2 x LOR 182
PosiTrac Plus contact element	2 x B10724-164
End plug (suffix Y)	EPR 10
Max. speed for PosiTrac Plus seal	1950 r/min
P60°	104 kN
P90°	62.3 kN
P120°	39.1 kN
P150°	35.6 kN
P180°	42.7 kN
Pa	15.3 kN
Mass pillow block	34 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	181.44 g