

# KOYO NA201 deep groove ball bearings

KOYO NA201 deep groove ball bearings Engineering Calculator , 9 Days Days to Ship Manufacturing Service . 90 d Get Your Free.

|                                      |  |
|--------------------------------------|--|
| Days to Ship                         | 9 Days                                     |
| d                                    | 90   |
| D                                    | 160  |
| B                                    | 30   |
| Precision (JIS)                      | Grade 0                                    |
| Number of Raceway Ring Rows          | Single Row                                 |
| Specifications/Environment           | Standard                                   |
| Basic Load Rating, Dynamic Rating(N) | 182000                                     |
| Internal Clearance Symbol            | CN (Normal Clearance)                      |
| Shaft Bore Config.                   | Cylindrical Bore                           |
| Format symbol                        | NU (double brims for the outer ring)       |
| Holder Symbol                        | No   |
| Specifications                       | Standard                                   |
| Symbol of Bearing Ring Shape         | No symbol: Internal diameter cylinder hole |
| Revolution Frequency(rpm)            | 3900                                       |
| Outer ring oil hole                  | Standard                                   |
| Large-capacity type                  | E (Large-capacity type)                    |
| Combination of two pieces            | Standard                                   |
| Cylinder shape (suffix symbol: X)    | No   |
| Raceway Ring Shape                   | Cylindrical Roller                         |

|                                     |                 |
|-------------------------------------|-----------------|
| Load Direction                      | Radial          |
| Inner/Outer Ring Material           | Steel           |
| Rolling Element Material            | Steel           |
| High-Speed Steel                    | Standard        |
| RoHS                                | 6               |
| I.D.(Ø)                             | 90              |
| O.D.(Ø)                             | 160             |
| Width(mm)                           | 30              |
| Size Standards                      | Metric System   |
| Outer Ring Type                     | Flat            |
| Retainer Type                       | Momi removing   |
| Rotational Speed(rpm)               | 4000            |
| Basic Load Rating, Static Rating(N) | 217000          |
| Clearance sign                      | No              |
| Accuracy(Class)                     | Class 0         |
| Bearing Ring Type                   | Type NU         |
| Acoustic Symbol                     | No              |
| Seal, Shield Symbols                | No              |
| Precision Grade Symbol              | No              |
| Symbol of contact angle             | No              |
| Special Configurations Code         | No              |
| Symbols of Lubrication Amount       | No              |
| Internal Symbol                     | No              |
| Outer Ring                          | With Outer Ring |
| Holder Color                        | No              |
| Low Torque Specification            | No              |
| Material Symbol                     | No              |