

KOYO NA5910 needle roller bearings

We work closely with our KOYO NA5910 needle roller bearings manufacturing partners to bring the 0.0 Inventory best N/A Minimum Buy Quantity value to customers.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	16 lb
EAN	0053893550503
Product Group	M06288
Component Description	Take Up Bearing Only
Rolling Element	Tapered Roller Bearing
Housing Style	Unit Only
Mounting Method	Concentric Collar
Compatible Take Up Frame	Not Specified
Adjustment Travel Length	0
Housing Material	Cast Iron
Other Features	Double Row Double Collar Wide Slot Two Lip Seal Electrodeposition Coating With Set Screw
Inch – Metric	Metric
Long Description	Take Up Bearing Only; 55MM Bore; 20.65MM Slot Width; 114.3MM Slot to Slot Distance; Tapered Roller B
UNSPSC	31171533

Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Take Up
Weight / LBS	16
d	2.165 Inch 55 Millimeter
Slot to Slot Distance	4.5 Inch 114.3 Millimeter
Slot Width	0.813 Inch 20.65 Millimeter
Shaft Size	2.165 in
Shaft Size Type	Metric
UPC Code	053893550503
Dimension B	3-3/4 in
Dimension L	7-1/8 in
Dimension A1	13/16 in
Dimension L3	3-3/4 in
Dimension L1	4-5/8 in
Dimension N	1-1/4 in
Dimension L2	1 in
Dimension N1	1-1/4 in
Dimension H2	3-7/8 in
Dimension N2	2-1/4 in
Dimension d1	3-3/4 in
Dimension H1	4-1/2 in
Dimension H	5-1/4 in
Dimension A2	2-9/16 in
e	0.36
X (if $F_a/F_r \leq e$)	0.87
Y (if $F_a/F_r \leq e$)	2.38
X (if $F_a/F_r > e$)	0.7
Y (if $F_a/F_r > e$)	2.87

K Factor	1.65
C90 Dynamic Load Rating ¹	10900 lb
C0 Static Load Rating	48200 lb
Fa-max Maximum Permissible Thrust Load ²	3454 lb
Fr-max Maximum Allowable Slip Fit Radial Load ³	8900 lb
Max. Speed ⁴	2730 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to