

KOYO NA5910 needle roller bearings

We work closely with our KOYO NA5910 needle roller bearings manufacturing partners to bring the 0.0 Inventory best N/A Minimum Buy Quantity value to customers.

| | |
|--------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 16 lb |
| EAN | 0053893550503 |
| Product Group | M06288 |
| Component Description | Take Up Bearing Only |
| Rolling Element | Tapered Roller Bearing |
| Housing Style | Unit Only |
| Mounting Method | Concentric Collar |
| Compatible Take Up Frame | Not Specified |
| Adjustment Travel Length | 0 |
| Housing Material | Cast Iron |
| Other Features | Double Row Double Collar Wide Slot Two Lip Seal Electrodeposition Coating With Set Screw |
| Inch – Metric | Metric |
| Long Description | Take Up Bearing Only; 55MM Bore; 20.65MM Slot Width; 114.3MM Slot to Slot Distance; Tapered Roller B |
| UNSPSC | 31171533 |

| | |
|--------------------------|-------------------------------|
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Take Up |
| Weight / LBS | 16 |
| d | 2.165 Inch 55 Millimeter |
| Slot to Slot Distance | 4.5 Inch 114.3 Millimeter |
| Slot Width | 0.813 Inch 20.65 Millimeter |
| Shaft Size | 2.165 in |
| Shaft Size Type | Metric |
| UPC Code | 053893550503 |
| Dimension B | 3-3/4 in |
| Dimension L | 7-1/8 in |
| Dimension A1 | 13/16 in |
| Dimension L3 | 3-3/4 in |
| Dimension L1 | 4-5/8 in |
| Dimension N | 1-1/4 in |
| Dimension L2 | 1 in |
| Dimension N1 | 1-1/4 in |
| Dimension H2 | 3-7/8 in |
| Dimension N2 | 2-1/4 in |
| Dimension d1 | 3-3/4 in |
| Dimension H1 | 4-1/2 in |
| Dimension H | 5-1/4 in |
| Dimension A2 | 2-9/16 in |
| e | 0.36 |
| X (if $F_a/F_r \leq e$) | 0.87 |
| Y (if $F_a/F_r \leq e$) | 2.38 |
| X (if $F_a/F_r > e$) | 0.7 |
| Y (if $F_a/F_r > e$) | 2.87 |

| | |
|--|---|
| K Factor | 1.65 |
| C90 Dynamic Load Rating ¹ | 10900 lb |
| C0 Static Load Rating | 48200 lb |
| Fa-max Maximum Permissible Thrust Load ² | 3454 lb |
| Fr-max Maximum Allowable Slip Fit Radial Load ³ | 8900 lb |
| Max. Speed ⁴ | 2730 rpm |
| Note | Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to |