

# KOYO NQ25/20 needle roller bearings

KOYO NQ25/20 needle roller bearings with easy-to-use parts graphics, giving you the ability to check parts availability, 239.713 mm da pricing, examine remanufactured options.

da	239.713 mm
Da	399.999 mm
Ca	117.805 mm
A1	222.25 mm
A2	304.8 mm
ba	96.838 mm
H	474.663 mm
H1	241.3 mm
H2	95.25 mm
J min.	628.65 mm
J max.	708.025 mm
J1	133.35 mm
L	831.85 mm
N1	41.275 mm
R1	130.175 mm
R2	46.831 mm
RG	1 NPT
PG	1/4 NPT
h	69.85 mm
Housing	SAF 052 KA
Bearing	23052 CCK/W33
Adapter sleeve assembly	SNP 3052×9.7/16

Stabilizing ring	2 x A8898
Labyrinth ring	2 x LOR 553
PosiTrac Plus contact element	2 x B10724-178
End plug (suffix Y)	X-5217-2
Max. speed for PosiTrac Plus seal	600 r/min
P60°	423 kN
P90°	254 kN
P120°	160 kN
P150°	145 kN
P180°	173 kN
Pa	81.4 kN
Mass pillow block	247 kg
Cap bolt	4 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	2749.95 g