

KOYO NQI20/16 needle roller bearings

KOYO NQI20/16 needle roller bearings Manufacturers , 480 Outer Diameter (mm) Online Wholesale 790x480x248 Size (mm) Suppliers 790 Bore Diameter (mm) !

Size (mm)	790x480x248
Bore Diameter (mm)	790
Outer Diameter (mm)	480
Width (mm)	248
d	480 mm
D	790 mm
B	248 mm
d2	579 mm
D1	692 mm
b	22.3 mm
K	12 mm
r1,2 – min.	7.5 mm
da – min.	500 mm
da – max.	579 mm
Da – max.	758 mm
ra – max.	6 mm
Basic dynamic load rating – C	7362 kN
Basic static load rating – C0	12000 kN
Fatigue load limit – Pu	780 kN
Reference speed	400 r/min
Limiting speed	750 r/min
Calculation factor – e	0.3

Calculation factor – Y1	2.3
Calculation factor – Y2	3.4
Calculation factor – Y0	2.2
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	514.899
EAN	7316576657146
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Bronze
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AH3196 A0HX3196 (Specify bore)
Withdrawal Nut	HM3196
Inch – Metric	Metric
Long Description	480MM Tapered Bore; 790MM Outside Diameter; 248MM Width; C0-Medium Clearance; Adapter Mount; Double
Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing

Keyword String	Spherical
Weight / LBS	1,135.159
Width	9.764 Inch 248 Millimeter
Adapter Part Number	SNP3196 (Specify bore) Inch H3196 (Specify bore) Millimeter
Bore	18.898 Inch 480 Millimeter
Outside Diameter	31.102 Inch 790 Millimeter
bore diameter:	480 mm
closure type:	Open
outside diameter:	790 mm
lubrication hole type:	Holes on Outer Ring
overall width:	248 mm
operating temperature range:	392 Degrees °F
bore type:	Tapered 1:12
cage material:	Bronze
outer ring type:	Not Split
application:	Heavy Duty
internal clearance:	C0
series:	Spherical Roller 231 Series
d2 ≈	579 mm
D1 ≈	692 mm
r1,2 min.	7.5 mm
Da max.	758 mm
ra max.	6 mm
Basic dynamic load rating C	7362 kN
Basic static load rating C0	12000 kN
Fatigue load limit Pu	780 kN
Calculation factor e	0.3
Calculation factor Y1	2.3

Calculation factor Y2	3.4
Calculation factor Y0	2.2
Mass bearing	470 kg