

# KOYO NU3306 cylindrical roller bearings

Offer High Quality Brand KOYO NU3306 cylindrical roller bearings .Contact Us 90 mm d Online to Get Best Quote.

d	90 mm
D	160 mm
B	30 mm
rs min	2 mm
Radial clearance class	C3
Mass	2.15 kg
Dynamic load, C	96 kN
Static load, C0	71.5 kN
Fatigue limit load, Cu	2.9 kN
f0	14.5
Nlim (grease)	4,000 rpm
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	170 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.45 Hz
Characteristic outer ring frequency, BPF0	4.11 Hz
Characteristic inner ring frequency, BPFI	5.89 Hz
da min	99 mm
Da max	151 mm
ra max	2 mm

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	0692314644249
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	90MM Bore; 160MM Outside Diameter; 30MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   IS
Other Features	Deep Groove   Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	4.9604
Bore	3.543 Inch   90 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	1.181 Inch   30 Millimeter

Outside Diameter

6.299 Inch | 160  
Millimeter