

KOYO NUP305 cylindrical roller bearings

KOYO NUP305 cylindrical roller bearings, Units and 72.619 mm Ca Housings CAD 210 mm Da models , Manufacturing Service . 127 mm da Get Your Free.

da	127 mm
Da	210 mm
Ca	72.619 mm
A1	120.65 mm
A2	187.325 mm
ba	53.975 mm
H	258.762 mm
H1	133.35 mm
H2	53.975 mm
J min.	336.55 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	79.375 mm
R2	30.163 mm
RG	1/2 NPT
PG	1/4 NPT
h	46.038 mm
Housing	SAF 028 KA
Bearing	23028 CCK/W33
Adapter sleeve assembly	SNW 3028×5

Stabilizing ring	2 x 36053-50
Labyrinth ring	2 x LOR 123
PosiTrac Plus contact element	2 x B10724-122
End plug (suffix Y)	EPR 27
Max. speed for PosiTrac Plus seal	1150 r/min
P60°	185 kN
P90°	111 kN
P120°	72.5 kN
P150°	66.7 kN
P180°	81.4 kN
Pa	22.2 kN
Mass pillow block	62.6 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	1220 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	379.89 g