

# KOYO NUP313 cylindrical roller bearings

KOYO NUP313 cylindrical roller bearings Product Brochures , Manufacturing Service . 0.0 Inventory Get Your Free.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REGAL BELoit   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 0.907  |
| EAN                       | 0662798252223  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw  |
| Housing Style             | 2 Bolt Tap Base Pillow Block   |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 7/16 Inch  |
| Relubricatable            | Yes  |
| Insert Part Number        | B250R  |
| Seals                     | Nitrile Rubber   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Single Row   Spherical   Anti Rotation Pin   Has Trash Guard   Smaller Housing             |
| Long Description          | 2 Bolt Tap Base Pillow Block; 1-1/4" Bore; 1-11/16" Base to Center Height; Set Screw Mount |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.40                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | 1001-07108                     |
| Manufacturer Internal Number  | 25222                          |
| Weight / LBS                  | 2                              |
| Nominal Bolt Center to Center | 3 Inch   76 Millimeter         |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter           |
| Actual Bolt Center to Center  | 3 Inch   76Millimeter          |
| d                             | 1.25 Inch   31.75 Millimeter   |
| D                             | 1.181 Inch   30 Millimeter     |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter           |
| B                             | 1.688 Inch   42.875 Millimeter |