

KOYO RF364825-1 needle roller bearings

Our highly-skilled and factory-trained service experts have the 0.0 Inventory resources to help you with all your KOYO RF364825-1 needle roller bearings needs – including routine maintenance, major repairs, warranty service, N/A Minimum Buy Quantity and equipment inspections.

| | |
|----------------------|---|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0.08 |
| EAN | 7316577089786 |
| Product Group | B04270 |
| Enclosure | Open |
| Precision Class | ABEC 7 ISO P4 |
| Material – Ball | Steel |
| Number of Bearings | 2 (1 Pair) |
| Contact Angle | 25 Degree |
| Preload | Light |
| Raceway Style | 1 Rib Outer Ring |
| Cage Material | Phenolic |
| Rolling Element | Ball Bearing |
| Mounting Arrangement | Duplex-Universal |
| Flush Ground | Yes |
| Inch – Metric | Metric |
| Other Features | Single Row Angular Contact High Precision |

| | |
|-------------------------------|---|
| Long Description | 17MM Bore; 35MM Outside Diameter; 20MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Ball |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact Ball |
| Manufacturer Item Number | 7003 ACD/P4ADGA |
| Weight / LBS | 0.183 |
| d | 0.669 Inch 17 Millimeter |
| B | 0.787 Inch 20 Millimeter |
| D | 1.378 Inch 35 Millimeter |
| bore diameter: | 17 mm |
| radial dynamic load capacity: | 6.5 kN |
| outside diameter: | 35 mm |
| radial static load capacity: | 3.1 kN |
| overall width: | 10 mm |
| bearing material: | Steel |
| contact angle: | 15 ° |
| maximum rpm: | 60000 RPM |
| internal clearance: | C0 |
| finish/coating: | Uncoated |
| ball screw application: | Not for Ball Screws |
| outer ring width: | 10 mm |
| closure type: | Open |
| fillet radius: | 0.3 mm |
| precision rating: | ABEC 7 (ISO Class 4) |
| series: | 70 |