

KOYO RV455325P needle roller bearings

Find the discount KOYO RV455325P needle roller bearings online you need . We offer ... If you check out our 110 Outer Diameter (mm) large selection of 60x110x22 Size (mm) KOYO RV455325P needle roller bearings once .

Size (mm)	60x110x22
Bore Diameter (mm)	60
Outer Diameter (mm)	110
Width (mm)	22
d	60 mm
D	110 mm
B	22 mm
C	22 mm
Angle (α)	25 °
a	36 mm
r min.	1,5 mm
r1 min.	1 mm
da min.	68,5 mm
db min	65,5 mm
ra max.	1,5 mm
Weight	0,765 Kg
Basic dynamic load rating (C)	61,5 kN
Basic static load rating (C0)	49 kN
(Grease) Lubrication Speed	6 600 r/min
Contact angle α	30 °
rs min	1.5 mm

r1s min	1 mm
Mass	0.76 kg
Dynamic load, C	61.5 kN
Static load, C0	49 kN
Fatigue limit load, Cu	2.23 kN
Nlim (oil)	8,800 rpm
Nlim (grease)	6,600 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
da min	68.5 mm
Da max	101.5 mm
Db max	104.5 mm
r1a max	1 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.782
Product Group	B04270
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	30 Degree
Internal Clearance	C0-Medium

Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	60MM Bore; 110MM Outside Diameter; 22MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Ba
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Outside Diameter	4.331 Inch 110 Millimeter
Width	0.866 Inch 22 Millimeter
Bore	2.362 Inch 60 Millimeter