

# KOYO UCTX11-35E bearing units

What is KOYO UCTX11-35E bearing units in mechanical engineering? 150 Outer Diameter (mm) Manufacturing Service . Upload your CAD file for an 100x150x39 Size (mm) instant.

Size (mm)	100x150x39
Bore Diameter (mm)	100
Outer Diameter (mm)	150
Width (mm)	39
d	100 mm
D	150 mm
T	39 mm
B	39 mm
C	32,5 mm
a	29,3 mm
r min.	2 mm
r1 min.	1,5 mm
da min.	112 mm
Da min	137 mm
Da max.	141 mm
db max.	107 mm
Db min.	143 mm
ra max.	2 mm
rb max.	1,5 mm
Weight	2,38 Kg
Basic dynamic load rating (C)	235 kN
Basic static load rating (C0)	405 kN
(Grease) Lubrication Speed	2200 r/min

(Oil) Lubrication Speed	3000 r/min
Calculation factor (e)	0,29
Calculation factor (Y0)	1,2
LangID	1
outer r	1.5
D_	150
TC-BET22	0
TC-BET21	2
TC-BET23	0
inner r	2
mass	2.38
GRS rpm	2200
D_b	143
Cr	24000
TC-RA	378
DE_	136.543
T-ALP23	0
db	107
T-ALP22	40
Prod_Type3	TRBSR_MD_A
da	112
T-ALP21	21
Iso	2CE
ALPHA_	10.833
SDM_	124.028
SBRG	30
D_a2	137
hidYobi	HR33020J
Y1	2.1

D_a1	141
B_	39
hidTable	ecat_NSTPRM
Oil rpm	3000
C0r	41500
Y0	1.2
TC-SLR	29.5
inner ra	2
outer rb	1.5
C0	405
Sa	7
Sb	6.5
e	0.29
DA_	12.68
Z_	29
C_	32.5
yobi	HR33020J
TC-DA1	13.194
TC-DA2	12.166
KBRG	3111
DI_	111.512